



KOOBOND

SKS 9600 Non-Staining Stone Silicone Sealant

One Component, Neutral Cure
Weatherproof, no distortion
Anti-crack, anti-leak
Stone Silicone

White, Black, Grey and matching colour provided
300ml/tube, 24tubes/ctn; 590ml/sausage, 20sausages/ctn

Stored in a dry and shade place, temperature below 27°C
12 months for shelf life

Certified company quality system according to ISO 9001
ISO 11400, OHSAS 18001 and BV certificate

Features

1. One component, easy to use.
2. Neutral cure, non-staining to substrates.
3. Excellent weatherproofing, virtually unaffected by sunlight, rain, snow, ozone.
4. Stable performance, properties remained within serviceable range of -40°C ~ +150°C, without brittle, crazing or cracking.

Scope of use

1. Specifically developed for weather-sealing joints for stone curtain walls and cladding, whilst minimizing any potential for staining to the stone.
2. Ideal for sealing requirement of anti-pollution for stone, glass, painted metal, concrete and other materials.
3. Weatherproofing sealing for Glass, stone, metal curtain wall; suitable for structural use.
4. The actual performance will depend on the actual base of material and using method.

Important notes

1. Use restrictions: total water immersion, such as the aquarium, swimming pool, need to use paint or architectural sealant application; in contact with bituminous-based material.
2. Avoid contact with skin and eyes, keep out of children's reach; in case of contact with skin or eyes, rinse clean with water immediately, please seek medical assistance if irritation persists.
3. Fully cured sealant is not hazardous.
4. Used in the well-ventilated environment.
5. Store in a dry and shade place, temperature below 27°C.

Application

1. Keep surface clean, dry and free of dust or grease.
2. Cover the surfaces with masking tape if necessary.
3. Rip off the tape before sealant cured.
4. Uncured sealant can be cleaned up by the cloth and solvent.
5. Use back-filling material to avoid three-sided adhesion.
6. The compatibility testing before using is required.

Contact

Tel: 0086 570 8598 517
Fax: 0086 570 8598 517
E-mail: annie@ztsilicone.com
Website: www.ztsilicone.com