

KOOBOND SKS 9800 Silicone Structural Sealant

One Component, Neutral Cure Weatherproof, no distortion Anti-crack, anti-leak

White, Black, Grey and macthing colour provided 300ml/tube, 24tubes/ctn; 590ml/sausage, 20sausage/ctn

Stored in a dry and shade place, temperature below 27°C 12 months for shelf life

Certified company quality system according to ISO 9001 ISO 11400, OHSAS 18001 and BV certificate

Features

- 1. One component, easy to use.
- 2. Neutral cure, non-corrosive to sensitive substrates.
- 3. Excellent weatherproofing, virtually unaffected by sunlight, rain, snow, ozone.
- 4. Stable performance, properties remained within serviceable range of -40 $^{\circ}$ C ~ +150 $^{\circ}$ C, without brittle, crazing or cracking.

Scope of use

- 1. Structural glazing adhesives.
- 2. Suitable for general glazing and caulking uses.
- 3. Suitable for sealing facades & claddings, EIFS, curtain walls and building construction applications.
- 4. Used in materials: glass, aluminum, brick, concrete, steel, ceramic, fiberglass, and most of construction materials sealing.
- 5. The actual performance will depend on the actual base of material and using method.

Important notes

- 1. Use restrictions: total water immersion, such as the aquarium, swimming pool, need to use paint, in contact with bituminous-based material.
- 2. Avoid contact with skin and eyes, keep out of children's reach; in case of contact with skin or eyes, rinse clean with water immediately, please seek medical assistance if irritation persists.
- 3. Fully cured sealant is not hazardous.
- 4. Used in the well-ventilated environment.
- 5. Store in a dry and shade place, temperature below 27°C.

Application

- 1. Keep surface clean, dry and free of dust or grease.
- 2. Cover the surfaces with masking tape if necessary.
- 3. Rip off the tape before sealant cured.
- 4. Uncured sealant can be cleaned up by the cloth and solvent.
- 5. Use back-filling material to avoid three-sided adhesion.
- 6. The compatibility testing before using is required.

Contact

Tel: 0086 570 8598 517 Fax: 0086 570 8598 517 E-mail: annie@ztsilicone.com Website: www.ztsilicone.com