



KOOBOND

SKS 9200 Multifunctional Silicone Sealant

One Component, Neutral Cure
Weatherproofing, Super flexible
Multifunctional Silicone

Translucent, White, Black, Grey and matching colour provided
300ml/tube, 24tubes/ctn, 64ctns/pallet

Stored in a dry and shade place, temperature below 27°C
12 months for shelf life

Certified company quality system according to ISO 9001
ISO 11400, OHSAS 18001 and BV certificate

Features

1. One Component, easy to use.
2. Neutral cure, non-corrosive to sensitive substrates.
3. Excellent weatherproofing, virtually unaffected by sunlight, rain, snow, ozone.

Scope of use

1. Weatherproofing, movement joints; facade panels, metal cladding, glazing & caulking.
2. Windows, doors & perimeter joints.
3. EIFS, non-structural building construction applications..
4. Used in materials: glass, aluminum, ceramics, metals & steels, fiberglass, most plastics vinyl windows, bricks, marble & granite concrete & masonry substrates, precast panels.
5. Please refer to the product technical data sheet for details.

Important notes

1. Use restrictions: total water immersion, such as the aquarium, swimming pool, need to use paint or architectural sealant application; in structural glazing; in contact with bituminous-based material.
2. Avoid contact with skin and eyes, keep out of children's reach; in case of contact with skin or eyes, rinse clean with water immediately, please seek medical assistance if irritation persists.
3. Fully cured sealant is not hazardous.
4. Used in the well-ventilated environment.
5. Store in a dry and shade place, temperature below 27°C.

Application

1. Keep surface clean, dry and free of dust or grease.
2. Cover the surfaces with masking tape if necessary.
3. Rip off the tape before sealant cured.
4. Uncured sealant can be cleaned up by the cloth and solvent.
5. Use back-filling material to avoid three-sided adhesion.
6. The compatibility testing before using is required.

Contact

Tel: 0086 570 8598 517

Fax: 0086 570 8598 517

E-mail: annie@ztsilicone.com

Website: www.ztsilicone.com