



KOOBOND SKS 968 Silicone Aquarium Sealant

One Component, Acetoxy Cure
Fast cure, high strength
Aquarium Silicone

Translucent, matching colour provided
300ml/tube, 24tubes/ctn, 64ctns/pallet

Stored in a dry and shade place, temperature below 27°C
12 months for shelf life

Certified company quality system according to ISO 9001
ISO 11400, OHSAS 18001 and BV certificate

Scope of use

1. Surfaces must be cleaned before applying sealant.
2. Apply between glass edges and as a fillet bead, 1/4 inch (6.35 millimeters) minimum, to gain maximum bond strength and structural integrity.
3. Maintain a permanent structural frame around the edges of tanks larger than 30 gallons to ensure integrity of the tank and seals.
4. Make sure all the sealant is fully cured before filling water.
5. After sealant cured, rinse with warm water and refill, then check PH twice during the next 24 hours before put the fish in.
6. The actual performance will depend on the actual base of material and using method.
7. Please refer to the product technical data sheet for details.

Important notes

1. Use restrictions: total water immersion, such as the aquarium, swimming pool, need to use paint or architectural sealant application; in structural glazing; in contact with bituminous-based material.
2. Avoid contact with skin and eyes, keep out of children's reach; in case of contact with skin or eyes, rinse clean with water immediately, please seek medical assistance if irritation persists.
3. Fully cured sealant is not hazardous.
4. Used in the well-ventilated environment.
5. Store in a dry and shade place, temperature below 27°C.

Application

1. Keep surface clean, dry and free of dust or grease.
2. Cover the surfaces with masking tape if necessary.
3. Rip off the tape before sealant cured.
4. Uncured sealant can be cleaned up by the cloth and solvent.
5. Use back-filling material to avoid three-sided adhesion.
6. The compatibility testing before using is required.

Contact

Tel: 0086 570 8598 517
Fax: 0086 570 8598 517
E-mail: annie@ztsilicone.com
Website: www.ztsilicone.com